

Aluminum Nitride Enabled MEMS for Near-Zero Power Wakeup and High Temperature Capable Sensing

Benjamin A. Griffin, Ph.D.
Defense Advanced Research Projects Agency

IEEE International Conference on Wireless for Space and Extreme Environments
Passive Wireless Sensor Technology Workshop
Huntsville, Alabama

December 12, 2018





Aluminum Nitride (AlN)

Piezoelectric thin film

Physical vapor deposited

- Low temperature deposition
~350°C

CMOS compatible

Non-ferroelectric

- No Curie temperature
- Texture achieved during deposition


Large band-gap (6 eV)

High temperature capable

- Melting point of 2,200°C
- Piezoelectric response has been measured at 1,150°C

Property	AlN
Low permittivity, ϵ_{33}^f	10.3
High sensitivity, g_{31} (V/m / Pa)	0.030
High signal-to-noise ratio ($\sqrt{\text{Pa}}$)	21×10^5
Low loss tangent, $\tan \delta$	0.003
Parallel piezo coefficient, d_{33} (pm/V)	5.5
Transverse piezo coefficient, d_{31} (pm/V)	-2.7

Columnar AlN



Griffin, B. A., Nordquist, C. D., and Henry, M. D., "Beyond Aluminum Nitride: Piezoelectric Materials for RF MEMS Resonators," presentation at the *International Microwave Symposium*, Honolulu, Hawaii, June 4-9, 2017




AlN Commercial Success

Bulk Acoustic Wave (BAW) Resonator Based Filters


- Half-wavelength, thickness mode resonators
- Filter frequency is set by film thickness
- Commercial success for AlN MEMS
- Greater than 60 total RF filters in the modern smartphone*

* 2015 Johnson, R. C., "Fabless RF Filters Cut Size, Share Same Die"
http://www.eetimes.com/document.asp?doc_id=1327528

Film Bulk Acoustic Resonator (FBAR)



Solidly Mounted Resonator (SMR)




Volume market for AlN-based MEMS established by mobile platforms





New Applications for AlN

Near-Zero Power Wakeup System

Piezoelectric Resonant Accelerometer




Long Channel 0.35 μm CMOS




XMEMS: High Temperature Capable MEMS

AlN/SiC-Based MEMS Process





XMEMS RF Resonator





N-ZERO Vision: OFF but ALERT!




N-ZERO passive sensor wake-up:

- Continuous operation and near-zero power processing
- Persistent sensing with greatly extended lifetime and reduced cost



N-ZERO Vibration Solution



Piezoelectric MEMS combined with a subthreshold-CMOS ASIC offers a near-zero power solution




Near-Zero Power Vibration Based Classifier


- Piezoelectric materials require zero input power to provide an electrical output signal
- High-Q resonance enables passive filtering in the mechanical energy domain
- Aluminum nitride sensors integrated with very-low power subthreshold CMOS
- Dual channel wakeup requires 5.25 nW in alert mode; 6.75 nW after wakeup

Near-Zero Power Wakeup System

Piezoelectric Resonant Accelerometer



Long Channel 0.35 μm CMOS






Near-Zero Power Vibration Based Classifier


Generator Vibration Profile

Physical Signal




Zero power signal filtering in the mechanical domain


5.25 nW, dual-channel
0.35 μm CMOS
comparator/latch



Passive, Piezoelectric, Frequency
Selective Sensors



Sensor
Electrical
Output





R. Reger et al.,
2018 "Two-Channel Wakeup System Employing Aluminum Nitride Based MEMS Resonant Accelerometers for Near-Zero Power Applications",
Hilton Head Workshop 2018: A Solid-State Sensors, Actuators and Microsystems Workshop, Hilton Head Island, June 3-7




Wakeup Accelerometer

AlN Vibration Sensor with Trimmable Resonant Frequency



Vibration Sensor Frequency Response



R. Reger et al.,
2018 "Two-Channel Wakeup System Employing Aluminum Nitride Based MEMS Resonant Accelerometers for Near-Zero Power Applications",
Hilton Head Workshop 2018: A Solid-State Sensors, Actuators and Microsystems Workshop, Hilton Head Island, June 3-7



- Matched resonant frequency to target signature within 0.1%
- Demonstrated frequencies as low as 43 Hz

Sensor Performance of Nearly 500 V/G and $Q > 12,500$



Vibration Classifier Block Diagram

- ASIC fabricated in 0.35 μm , trench isolated SOI using long channel (1:10) transistors operating subthreshold
- Each ASIC contains two comparator/latch circuits followed by digital logic




R. Reger et al.,
2018 "Two-Channel Wakeup System Employing Aluminum Nitride Based MEMS Resonant Accelerometers for Near-Zero Power Applications",
Hilton Head Workshop 2018: A Solid-State Sensors, Actuators and Microsystems Workshop, Hilton Head Island, June 3-7

Additional Channels Add Additional Power Consumption of 2.5 nW/Channel




Near-Zero-Power Vibration Classifier Testing

2-Channel Vibration Sensor Microsystem



- Field testing revealed **100% POD** and **0% FA** up to **0.18 m** from generator




Microsystem Measured Performance




New Applications for AlN

Near-Zero Power Wakeup System

Piezoelectric Resonant Accelerometer




Long Channel 0.35 μm CMOS




XMEMS: High Temperature Capable MEMS

AlN/SiC-Based MEMS Process



XMEMS RF Resonator






Sensor Systems for Extreme Environments

Objective: develop material set to enable extreme temperature capable transducers, control electronics, packaging solutions, wireless communication, etc.

Applications for sensor systems that can withstand extreme temperatures

- Gas turbines (1250°C)
- Hypersonic flight research (755°C)
- Automotive engines (300-1000°C)
- Nuclear power plant (300°C)
- Coal power plants (700°C)



Griffin, B. A., Habermehl, S. D., and Clews, P. J., "XMEMS: An Aluminum Nitride and Silicon Carbide MEMS Process for High Temperature Capable Transducers," presentation at *Material Science & Technology: Advanced Materials for Harsh Environments*, Columbus, Ohio, October 4-8, 2015



Current Approach

Turbine Engines

- Approach: open loop operating conditions are set off peak-performance to allow margins of safety to prevent surge/stall
- Lack of knowledge of the hot zone increases development time
- Extracting overall potential performance gains out of a highly coupled system is a large task
- Limitations: conventional sensing technologies are non-options
 - Silicon based electronics $< 250\text{ }^{\circ}\text{C}$
 - Cooling infrastructure incurs too much weight and cost
 - Connector failures lead to no fault found aircraft downtime



<http://www.aero-news.net>


Sensing in the hot zone will enable adaptive controls, shorter development cycles, and condition based maintenance for next generation turbine engines




Impact on National Security

Turbine Engines

- Increased stand-off distance for aircraft from carriers and bases
- Tradeoff between increased payload and range
- Potential for higher prime power
- Dynamic performance
- Fuel savings



http://cset.mnsu.edu/engagethermo/components_gasturbine.html



Enable enhanced performance for future DoD systems



Wide Bandgap Approach

Wide band gap (WBG: SiC, GaN, etc.) and ultra-wide band gap (UWBG: AlGaN/AlN, Diamond, etc.) semiconductor and MEMS materials can survive and operate through high temperature environments enabling direct sensing in the hot zone


Conventional silicon (1.1 eV) electronics < 250°C

WBG Silicon Carbide

- Material temperature limit > 2,500°C (sublimates)
- Bandgap 3.3 eV (4H)
- Electronics temperature limit: $\geq 800^{\circ}\text{C}$ (demonstrated)

UWBG Aluminum Nitride

- Melting point of 2,200°C
- Piezoelectric response measured at 1,150°C
- Bandgap 6.0 eV
- Electronics temperature limit: $\geq 1000^{\circ}\text{C}$ (theoretical)



Griffin, B. A., et al., "Development of an aluminum nitride-silicon carbide material set for high-temperature sensor applications," *Proceedings SPIE*, Baltimore, MD, 6/5/2014

WBG and UWBG materials enable higher temperature capable MEMS and electronics





High Temperature Capable Material Set

Aluminum nitride (AlN) piezoelectric thin film
Silicon carbide (SiC) structural film and wafer

- Sublimates at $>2500^{\circ}\text{C}$
- Coefficient of thermal expansion nearly matched to AlN

High temperature capable electrodes

- Titanium/Titanium nitride (Ti/TiN)
 - CMOS compatible



Griffin, B. A., Habermehl, S. D., and Clews, P. J., "XMEMS: An Aluminum Nitride and Silicon Carbide MEMS Process for High Temperature Capable Transducers," presentation at *Material Science & Technology: Advanced Materials for Harsh Environments*, Columbus, Ohio, October 4-8, 2015




Annealed AlN Alignment


Anneal of AlN on titanium / titanium nitride bottom metal electrode at 950°C for 3 hr

- X-Ray diffraction measurements to determine if AlN is still columnar
- In general, the goal is $<2^\circ$

Dipole Alignment




Ideal




Reality

Before



After






Griffin, B. A., Habermehl, S. D., and Clews, P. J., "XMEMS: An Aluminum Nitride and Silicon Carbide MEMS Process for High Temperature Capable Transducers," presentation at *Material Science & Technology: Advanced Materials for Harsh Environments*, Columbus, Ohio, October 4-8, 2015



XMEMS Resonator

- Survived rapid thermal anneal at 935°C, <1 Torr Argon, for 5 minutes before heated chuck testing in air
- Operation in air up to 500 °C





Technical Challenges

Electronics/MEMS

- Large bandgap to minimize intrinsic doping concentration at temperature (E_g vs kT)
- Thermal stresses
- High quality metal contacts
- For III-Vs, reactions/oxidations
- Thermal leakage power

Packaging



- Materials that can survive and operate through the high temperature environment

Communication

- Free-space: wireless RF or free-space optics
- Directed: multiplexed routing via optical or RF waveguides; ultrasonic communication

Power


- Powered via comms channel or harvest energy (i.e., thermal, vibration) from the environment



Complete solutions must address challenges facing the entire sensing system



High Temperature Electronics Landscape



Demonstrate full-functioning sensor systems at high temperatures



www.darpa.mil